

Technical Code DVS 2205-1 Supplement 8

Calculation of tanks and apparatus made of thermoplastics – characteristic values for the material group unplasticized polyamide

Technical Committee of the DVS

Working Group W 4 „Joining Plastics“

Subgroup W 4 3b „Structural Design - Apparatus Engineering“

This publication has been drawn up by a group of experienced specialists working in an honorary capacity and its consideration is recommended. The user should always check to what extent the contents are applicable to his particular case and whether the version on hand is still valid. No liability can be accepted by the DVS – German Welding Society and those participating in the drawing up of the document.

Content

1.	PA-U 12 180	3
1.1.	Time-to-rupture curves for PA-U 12 180 pipes.....	3
1.2.	Isochronous tension/elongation diagram of PA-U 12 180 for 23° C.....	3
1.3.	Creep modulus curves.....	7
1.3.1.	Creep modulus of PA-U 12 180 for 1 year.....	7
1.3.2.	Creep modulus of PA-U 12 180 for 10 years.....	8
1.3.3.	Creep modulus of PA-U 12 180 for 25 years.....	9
2.	Reduction factors (toughness coefficient) A1 for moulding materials made from PA-U 12 180	10
3.	Influence of moisture absorbency	11
3.1.	Moisture-dependent short-term modulus of elasticity of PA-U 12 180.....	11
3.2.	Moisture-dependent creep modulus curves of PA-U 12 180 for 1, 10 and 25 years....	12
3.2.1.	Moisture-dependent creep modulus curves of PA-U 12 180 for 1 year.....	13
3.2.2.	Moisture-dependent creep modulus curves of PA-U 12 180 for 10 years.....	14
3.2.3.	Moisture-dependent creep modulus curves of PA-U 12 180 for 25 years.....	15
4.	Creep modulus E_c for 100 min for PA-U 12 180	16
5.	Resistance to slow crack growth	17
6.	Influence of media on PA-U 12 180	17
7.	Literature	18
7.1.	Regulations.....	18
7.2.	Literature.....	18