

Technical (od/ DVS 22 5-1 Supple nent of

Technical Code DVS 2205-/ Supplement 8

Calculation of tanks and apparatus made of thermoplastics – characteristic values for the material group unplasticized polyamide

Technical Comittee of the DYS

Working Group W 4 "Joining Plastics"

Subgroup W 4 3b "Structu al Design - Apparatus Engineering"

This chi' ation has been drawn up by a group of experienced specialists working in an honorary capacity and its consideration is recommended. The user should always check to what extent the contents are applicable to his particular case and where the version on hand is still valid. No liability can be accepted by the DVS – German Welding Society and those participating in the drawing up of the document.

Content

1.	PA-U 12 180	3
1.1.	Time-to-rupture curves for PA-U 12 180 pipes	
1.2.	Isochronous tension/elongation diagram of PA-U 12 180 for 23° C	
1.3.	Creep modulus curves	
1.3.1.	Creep modulus of PA-U 12 180 for 1 year	7
1.3.2.		
1.3.3.	Creep modulus of PA-U 12 180 for 10 years	9
1.0.0.	Group modulus of 1770 of 12 100 for 20 yours	
2.	Reduction factors (toughness coefficient) A1 for moulding materials	
	made from PA-U 12 180	10
3.	Influence of moisture absorbency	11
3.1.	Moisture-dependent short-term modulus of elasticity of PA-U 12 120	11
3.2.	Moisture-dependent creep modulus curves of PA-U 12 180 fc (1, 10 and 25 years	s 12
3.2.1.	Moisture-dependent creep modulus curves of PA-U 12 180 for vea	
3.2.2.	Moisture-dependent creep modulus curves of PA-U 12 185 to 10 years	
3.2.3.	Moisture-dependent creep modulus curves of PA-U 12 130 for a years	
0.2.0.	Wolstare-acpendent Greep modulus curves of 174-0-12 110 for 14 years	10
4.	Creep modulus E _c for 100 min for PA-U 12 180	16
••		
5.	Resistance to slow crack growth	17
.		
6.	Influence of media on PA-U 12 180	17
7.	Literature	18
7.1.	Regulations	
7.2.	Literature	18