

Technical Code DVS 2216-1

Ultrasonic joining of moulded components and semi-finished products of thermoplastic materials in large-scale production - process description, machines and equipment, variables, design, quality assurance

DVS, Technical Committee, Working Group "Joining of Plastics"

This publication has been drawn up by a group of experienced specialists working in an honorary capacity and its consideration as an important source of information is recommended. The user should always check to what extent the contents are applicable to his particular case and whether the version on hand is still valid. No liability can be accepted by the Deutscher Verband für Schweißen und verwandte Verfahren e.V., and those participating in the drawing up of the document

Content:

- 1. Scope of application**
- 2. Area of application of the joining technique using ultrasound**
- 3. Process**
 - 3.1. Process description
 - 3.2. Characteristic variables
 - 3.3. Process parameters
 - 3.4. Process phases
 - 3.4.1. Process Phase 1, initial melting of the energy director (ED)
 - 3.4.2. Process Phase 2, unsteady melt formation
 - 3.4.3. Process Phase 3, quasi-steady melting-off phase
 - 3.4.4. Process Phase 4, holding phase / cooling phase
- 4. Machines, devices and tools**
 - 4.1. Structure and operating mode
 - 4.1.1. Schematic structure of an ultrasonic welding machine
 - 4.1.2. Ultrasonic generator
 - 4.1.3. Ultrasonic transducer
 - 4.1.4. Transformation piece
 - 4.1.5. Sonotrode
 - 4.1.6. Holder tool
 - 4.2. Types of welding devices and machines
 - 4.2.1. Requirements
 - 4.2.2. Devices with a manual drive
 - 4.2.3. Welding presses with a pneumatic drive
 - 4.2.4. Welding presses with an electric motor drive
 - 4.2.5. Custom-built machines
- 5. Safety measures**
- 6. Influence of the material properties on the welding behaviour**
 - 6.1. Shear modulus G' and mechanical loss factor $\tan \delta$ depending on the temperature
 - 6.2. Specific heat capacity c_p and the heat content
 - 6.3. Melting temperature range
 - 6.4. Viscosity of the melt (MFR or MVR)
 - 6.4.1. Reinforcing materials, fillers and other additives
- 7. Influence of the manufacturing conditions on the welding behaviour of the joining parts**
 - 7.1. Requirements on the joining parts
 - 7.1.1. Influence of moisture
 - 7.1.2. Regenerate and recycle
 - 7.1.3. Mould release agents
 - 7.1.4. Storage
- 8. Structural designing of the joining parts**
 - 8.1. General design-related characteristics
 - 8.1.1. Rounding-off of corners and edges
 - 8.1.2. Position of the joining parts and the distance away from the sonotrode (near and far field welding)
 - 8.1.3. Size and formation of the joining faces
 - 8.1.4. Energy directors